

## PRE-WIRED ELECTRONIC CONTROL BOARD

### **3PW BOX (three loops detector)** code 2302A110SW3PW

The version PW3 box has those features:

One 14 in. x 12in. x 6in fiberglass (large box 16in x 14in x 6in on request)  
with ON/OFF switch and 115 V receptacle.

Two loop detectors wired plus a third loop detector wired as a "shadow" (intermediate).

While the operator motor is running, the shadow loop will detect. Once the motor shuts off (pause), the shadow becomes live. Located under the closed gate, the shadow works along with the order safety loops to protect the vehicle within the path of the gate during closing.

One control panel *SWING PRO* (115 or 230 VAC).

Wiring map indicating wire input.

Open/Hold-Open contacts provide the normally open input for phone, fireboxes or any other Open/Hold-Open devices.

A plug outlet for any 115 VAC accessories and tools (5amp max).

An ON/OFF switch controlling power to control panel, accessories and plug outlet.

One plug-in receiver.

A push button to set the control panel.

Wired for dual photocells safety - open and closed.

Motors to terminal strip.

All components are compliant to UL 325.

Spike Suppressor: 20000 Amps and near lightning protection with modular omni surge suppressor.

Internal dimensions: large box 16" x 14" x 6"  
std box 14" x 12" x 6"

